



iPower All-in-one Hybrid Storage System

iPower HES-3000/3680/4600/5000/6000

The LIVOLTEK iPower HES Series is a premium all-in-one solar and storage solution that integrates a hybrid inverter with low-voltage batteries. This integration helps you reduce electricity bills and maximize energy independence from the grid. Key benefits include improved energy capture from PV modules, a space-saving compact design, and a sleek appearance that enhances your home's aesthetics. Additionally, the plug-and-play functionality and free online monitoring enable faster installation, quick site mapping to the monitoring platform, and easier maintenance with minimal effort.




Features

- Flexible and easy to expand
- Natural cooling, extremely quiet
- 150% oversized, 150% yield
- Smart and easy operation
- Intelligent charging and active balance
- Fanless design, quiet and long lifespan



Elegant Modular
and Unified Design



Flexible Storage
Capacity up to 25 kWh



Export Control and
Time-of-use Shifting



Maximized
Self-consumption

Compatible Products



Residential Lithium Battery



Smart EV Charger



Wi-Fi Dongle



Smart Meter



Monitoring System

Specifications

Inverter Model	Hyper-3000	Hyper-3680	Hyper-4600	Hyper-5000	Hyper-6000
PV Input					
Max. PV Input Power	4500Wp	5520Wp	6900Wp	7500Wp	7500Wp
Max. PV Input Voltage	600V				
MPPT Voltage Range	125~550V				
Max. PV Current	14A	14/14A	14/14A	14/14A	14/14A
Max. Short Circuit Current	17.5A	17.5/17.5A	17.5/17.5A	17.5/17.5A	17.5/17.5A
No. of MPPTs/Strings per MPPT	1/1	2/1	2/1	2/1	2/1
AC Output @ Grid					
AC Input Voltage Range/Frequency	186~290Vac/50Hz or 60Hz				
Nominal AC Power	3000W	3680W	4600W	5000W	6000W
Nominal AC Current	13.0A	16.0A	20.0A	21.7A	26.1A
THDi,Rated Power[%]	<3%				
EPS Output @ Off Grid					
EPS Output Voltage/Frequency	220Vac/50Hz or 60Hz				
Continuous Output Power (@25C)	3kVA	3.68kVA	4.6kVA	5kVA	6kVA
EPS Output Current	13.0A	16.0A	20.0A	21.7A	26.1A
Peak Power	1.1 x Pnom, 60 Sec; 1.5 x Pnom, 100ms				
Power Factor	~1 (Adjustable from 0.8 Leading to 0.8 Lagging)				
Waveform	Pure Sinusoidal Wave				
THDv,Rated Power[%]	<3%				
Battery Input					
Battery Type	Lithium Battery				
Battery Voltage	40~60V				
Galvanic Isolation for Battery	Yes				
Max.Charge Current of Inverter	60A	80A	100A	100A	125A
Max.Discharge Current of Inverter	60A	80A	100A	100A	125A
BMS Communication	CAN				
Protection	Over Voltage, Under Voltage, Over Current, Short Circuit, Over Temperature				
Efficiency					
Max. Efficiency	97.6%	97.8%			
Euro Efficiency	97.1%	97.4%			
Battery Model	BLF51-5				
Cell Type	LFP				
Nominal Energy	5kWh				
Max. Depth of Discharge	90%				
Nominal Voltage	51.2V				
Operating Voltage Range	40-58.4V				
Nominal Capacity	100Ah				
Max. Charge Current	50A				
Max. Discharge Current	100A				
Scalability	Up to 5 Modules/25kWh				
General Data					
Dimension (W*H*D)	415*1380*165mm				
Weight	85kg	86kg	87kg	87kg	87kg
Standard Warranty	10 Years				